

IP65 Macro Waterproof LED Luminaire



Features

- Up to 150lm/W ultra efficiency
- Easy maintenance with replaceable Odsel T8 LED Tubes
- IP65 polycarbonate diffuser and polycarbonate body
- 0.5mm² halogen free cables
- Up to %50 energy saving
- Active PFC >0.9
- Aluminum heatsink
- Shock proof PC front cover
- EN60598 certified
- 3000K, 4000K, 6500K, CRI >80
- Min 50.000 on/off cycles

Applications


- Factory, storage areas, carpark, cold storage, low bay areas

Options

- 2700K, 5700K

⊕ ⊖ IK08 IP65 CE 850°C

Light Distributions



Product ID	Input Voltage V	Power	PFC	Life Hrs	Operating Temp.		Light Flux	Dimensions			Weight
					-30C	+45C		A	B	C	
2005-118-EC	100-240V	8.5W	0.90	40.000	-30C	+45C	1050LM	660	86	90	900gr
2005-218-EC	100-240V	17.0W	0.90	40.000	-30C	+45C	2000LM	660	106	90	1600gr
2005-136-EC	100-240V	18.0W	0.90	40.000	-30C	+45C	2100LM	1270	86	90	1800gr
2005-236-EC	100-240V	36.0W	0.95	40.000	-30C	+45C	4000LM	1270	106	90	2500gr
2005-158-HL	100-240V	20.0W	0.95	40.000	-30C	+45C	2700LM	1570	86	90	2000gr
2005-258-HL	100-240V	40.0W	0.95	40.000	-30C	+45C	5300LM	1570	106	90	3200gr

Dimensions

