

# IP65 HE Waterproof LED Luminaire



## Features

- Up to 160 lm/W efficacy
- Flicker-free
- IP65
- Up to 16300 lm
- Up to %50 energy saving
- Active PFC >0.9 and low THD
- Aluminum heatsink
- Shock proof PC front cover
- H05SSF input cable
- EN60598 certified
- 3000K, 4000K, 6500K, CRI >80
- Min 50.000 on/off cycles

## Applications


- Factory, storage areas, carpark, cold storage

## Options


- 2700K, 5700K
- 90 CRI
- Custom cable length, connector
- DALI

⊕ ⊖ IK08 IP65 CE 850°C

## Light Distributions



Opaque



Transparent

Product ID	Input Voltage V	Power	PFC	Life Hrs	Operating Temp	Light Flux	Dimensions			Weight	Front Lens
							A	B	C		
HE06-084-XXFIG	220-240V	17.0W	0.90	50.000	-30C +45C	2300LM	655	32	54	400gr	Opaque
HE09-105-XXFIG	220-240V	27.0W	0.90	50.000	-30C +45C	3750LM	894	32	54	500gr	Opaque
HE12-200-XXFIG	220-240V	36.0W	0.90	50.000	-30C +45C	5100LM	1210	32	54	800gr	Opaque
HE12-200-XXTIG	220-240V	36.0W	0.90	50.000	-30C +45C	5600LM	1210	32	54	800gr	Transp.
HE15-285-XXFIG	220-240V	50.0W	0.90	50.000	-30C +45C	7400LM	1540	32	54	1000gr	Opaque
HE15-285-XXTIG	220-240V	50.0W	0.90	50.000	-30C +45C	8150LM	1540	32	54	1000gr	Transp.
HE15-301-XXTIG	220-240V	74.0W	0.90	50.000	-30C +45C	12550LM	1540	32	54	1100gr	Transp.
HE15-285-XXFI2	220-240V	100W	0.90	50.000	-30C +45C	14800LM	1540	97	54	2100gr	Opaque
HE15-285-XXTI2	220-240V	100W	0.90	50.000	-30C +45C	16300LM	1540	97	54	2100gr	Transp.

## Dimensions

